

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 826.1535/JDH

First Named Inventor or Application Identifier:

Hironori KANNO, et al.

Express Mail Label No.

 Jc408 U.S. PTO
 09/24/99
 02/04/99
APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

 ADDRESS TO: **Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231**

1. ☒ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract [Total Pages: 38]
3. ☒ Drawing(s) (35 USC 113) [Total Sheets: 14]
4. ☒ Oath or Declaration [Total Pages: 4]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation by Reference (usable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application, status still proper and desired.
15. ☒ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐ Other:

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: / **18. CORRESPONDENCE ADDRESS**
 STAAS & HALSEY
 Attn: James D. Halsey, Jr.
 700 Eleventh Street, N.W., Suite 500
 Washington, DC 20001

 Telephone: (202) 434-1500
 Facsimile: (202) 434-1501

APPLICATION FOR

UNITED STATES LETTERS PATENT

SPECIFICATION

Inventor(s): Hironori KANNO, Yoshiyuki HIRASHIMA
and Mikio FURUYAMA

Title of the Invention: SLIDE SHOW SYSTEM AND METHOD USING
A BROWSER

Slide Show System and Method using a Browser

Background of the Invention

Field of the Invention

5 The present invention is related to a slide show system and its method for performing a slide show using screen information obtained by a browser, in a browser system which refers to an information network such as a WWW (World Wide Web) which is a currently
10 a main source of information on the Internet.

Description of the Related Art

 The Internet is realized by connecting a plurality of computers via a communication network. A world-
15 wide information network which is realized by the Internet is named a WWW system. Recently, as an amount of information transmission increases over the WWW system, various kinds of multi-media information have been provided on the Internet.

20 A page of the WWW (a web page) is a unit of the multi-media information to be provided on the WWW, and is composed of an HTML (HyperText Markup Language) document and related data which are stored in an arbitrary WWW server. The WWW server transmits this
25 web page to a browser provided on a WWW client

according to an HTTP (HyperText Transfer Protocol).
The WWW browser displays the thus-received web page
on a screen of the WWW client.

The web page generally can provide text
5 information composed of character data, image
information composed of graphic data, audio
information, animation information or the like to a
user by using the HTML. Therefore, here, the display
of a web page includes not only the outputting of text
10 information or image information but also the
outputting audio information, animation information
or the like, which is included in the web page.

In order that a user accesses such information, it
is necessary to input address information which
15 uniquely represents a server and an HTML document
storing that information. This address information is
composed of several character strings and is named a
URL (Uniform Resource Locator).

However, it is difficult for a user to remember a
20 complicated URL composed of several tens of characters
for a long time. Further, in a case where a
predetermined page is required to be referred to many
times, it is neither convenient nor effective to type
this URL every time. Therefore, in order to easily
25 display a web page, a WWW browser is generally

provided with a function named a bookmark.

The bookmark function is to register a site which a user is fond of and a page which is frequently accessed, in a browser. The user first registers the URL of a page to be displayed as a bookmark. Then, at the time of accessing, the user displays a list of pages which are registered as bookmarks, and selects a desired page by clicking a mouse. Thus, the user can display his or her desired page without inputting a complicated URL.

Fig. 1 shows an example of a representative bookmark display screen. As shown in Fig. 1, a set of bookmarks 2 can be stored in a folder 1, and the bookmarks 2 are hierarchically managed.

In a folder "Lookup", bookmarks 2 such as "People" and "Yellow Pages" are registered. These bookmarks 2 are list-displayed by clicking the folder "Lookup". The user selects a desired page by double-clicking a line (an object) indicating the bookmark 2 such as "People" or the like so that he or she can display the desired page on a screen.

However, there arise the following problems about the above-mentioned conventional WWW browser:

Recently, as the functions of a portable personal computer become enhanced and its cost decreases, a lot

of presentations and conferences have taken place using such a personal computer. When such presentations or conferences take place, information of a web page is frequently displayed by connecting
5 the personal computer to the Internet.

However, there are a lot of cases where time is greatly restricted when a presentation or a conference is taking place. Therefore, it is neither convenient nor effective to type the above-mentioned URL every
10 time. Therefore, it is thought that the bookmark function is used as a method of quickly displaying a web page. However, this case also requires a lot of effort to display a list of bookmarks and to click the bookmark of a desired page each time, so that it takes
15 a predetermined operation time period to display a page in a browser.

There is a case where a speaker explains pages changing some pages every few minutes according to the contents of a presentation. In this case, it is
20 necessary to type a URL or select a bookmark whenever changing pages, so that a sufficient explanation cannot be given since the speaker spends a lot of time for operation of the browser system.

25 **Summary of the invention**

An object of the present invention is to provide a slide show system and method for easily and effectively displaying information of one or more web pages, thereby performing an effective slide show, when a presentation or a conference is taking place, in a browser system which refers to a WWW system.

The slide show system in a first aspect of the present invention includes a browser unit and a control unit.

The browser unit obtains information using address information defined on an information network and outputs the thus-obtained information. The control unit informs the address information to the browser unit according to a predetermined output sequence and instructs the output of information corresponding to the thus-informed address information.

Further, a program for causing a computer to perform a processing is stored in a storage medium in a second aspect of the present invention.

This processing includes a step of referring to a correspondence relationship between one or more pieces of address information defined on the information network and a sequence number representing a predetermined output sequence, and a step of informing the address information corresponding to the current

sequence number to the browser unit so that the output of information corresponding to the thus-informed address information is instructed.

Further, a program for causing a computer to perform a processing is stored in a storage medium in a third aspect of the present invention.

This processing includes a step of referring to a correspondence relationship between one or more pieces of address information defined on the information network and a sequence number representing a predetermined output sequence, a step of obtaining information using the address information corresponding to the current sequence number, and a step of outputting the thus-obtained information.

Brief Description of the Drawing:

Fig. 1 is a diagram showing a conventional bookmark display screen;

Fig. 2A is a principle diagram showing the slide show system according to the present invention;

Fig. 2B is a diagram showing the configuration of the slide show system;

Fig. 3 is a diagram showing a bookmark page;

Fig. 4 is a diagram showing a slide show screen;

Fig. 5 is a diagram showing a first operation

control parameter file;

Fig. 6 is a diagram showing a bookmark data file;

Fig. 7 is a flowchart showing display control processing;

5 Fig. 8 is a flowchart showing processing to be performed by a browser;

Fig. 9 is a flowchart showing first automatic processing;

10 Fig. 10 is a diagram showing a second operation control parameter file;

Fig. 11 is a flowchart showing second automatic processing;

Fig. 12 is a diagram showing the configuration of an information processing device; and

15 Fig. 13 is a diagram showing storage media.

Description of the Preferred Embodiments:

20 The preferred embodiments of the present invention will be explained in detail below with reference to the drawings.

Fig. 2A is a principle diagram of the preferred embodiments of the present invention. The slide show system shown in Fig. 2A includes a browser unit 11 and a control unit 12.

25 The browser unit 11 obtains information using the

address information defined on an information network,
and outputs the thus-obtained information. The control
unit 12 informs the address information to the browser
unit 11 according to a predetermined output sequence,
5 and instructs the browser unit 11 to output
information corresponding to the thus-informed
information.

The address information defined on the information
network corresponds to, for example, the URL defined
10 on a WWW system. The information obtained using the
address information corresponds to, for example, the
multi-media information of a web page.

The output sequence of information is
predetermined by preparing a correspondence
15 relationship between one or more pieces of the address
information and a sequence number. The control unit
12 informs the address information corresponding to
the current sequence number to the browser unit 11,
according to this output sequence. Thus, the browser
20 unit 11 obtains information using the thus-informed
address information, and can output the thus-obtained
information.

When the current sequence number is updated, new
address information is informed from the control unit
25 12 to the browser unit 11, and new information is

outputted. By repeating these operations, information of web pages to be outputted is sequentially updated so that a slide show can be performed by using the web pages.

5 According to this slide show system, the control unit 12 informs the address information to the browser unit 11 according to the output sequence so that a user need not type a URL nor select a bookmark whenever pages are switched. Therefore, the user can
10 concentrate on the explanation of the displayed information.

 For example, the browser unit 11 shown in Fig. 2A corresponds to a WWW browser 33, a display device 24, and a speaker 25 shown in Fig. 2B, which will be
15 described later. The control unit 12 shown in Fig. 2A corresponds to a slide show processing unit 31 shown in Fig. 2B.

 In the slide show system of the present embodiments, the following four functions are provided
20 for the presentation to be performed using a WWW browser:

 Function 1: instructing a display sequence of the URLs which are registered in a bookmark list, using a slide operation button (manual mode)

25 Function 2: automatically causing a browser to

display a plurality of pages in predetermined sequence and intervals using the URLs registered in a bookmark list (automatic mode)

Function 3: automatically generating background music (BGM) and a narration

Function 4: after downloading a web page to be displayed at a slide show, storing this page as a local file, and executing the above-mentioned Functions 1 and 2 using this local file

By being provided with the manual mode of Function 1, a user can perform a presentation manually switching pages like the performance of a slide show. Further, by being provided with the automatic mode of Function 2, a user can automatically switch pages without performing manual operations. Therefore, a user can concentrate on the explanation of displayed information.

Further, by being provided with Function 3, more effective presentation can be performed, and a narration can act as necessary explanation. Still further, by being provided with Function 4, a browser need not be connected to the Internet at that occasion so that a presentation can refrain from being interrupted by a connection failure.

Fig. 2B is a configuration diagram showing a slide

show system of the present embodiment. The slide show system shown in Fig. 2B is composed of a processing device 21, a data storage device 22, an input device 23, a display device 24, and a speaker 25. These devices are connected to each other via a bus 26.

The input device 23 corresponds to a pointing device such as a keyboard, a mouse or the like, or a touch panel and inputs instructions and data transmitted from a user to the programs executed by the processing device 21. The display device 24 corresponds to, for example, a CRT (cathode ray tube) display, and displays a screen of questions made from a program to the user, processing results, a web page, or the like.

The processing device 21 consists of a slide show processing unit 31, a network interface unit 32, and a WWW browser 33, and is connected to the Internet 27 via the network interface unit 32. An arbitrary method such as a dial-up connection to be performed via a public line, an exclusive line connection using an exclusive line or the like is used as a connection method.

Here, the slide show processing unit 31 and the data storage device 22 (parts encircled by a dotted line) of the processing device 21 mainly perform the

above-mentioned functions 1 to 4 of the slide show system. The slide show processing unit 31 includes an operation control parameter edition unit 41, a bookmark registration unit 42, a bookmark display control unit 43, an automatic calling unit 44, a web page display control unit 45, a BGM control unit 46, and a narration control unit 47. The data storage unit 22 stores an operation control parameter file 51, a bookmark data file 52, and a web page data file 53.

The slide show processing unit 31 corresponds to software components described by programs, and expands the function of the WWW browser 33 by being included as a function of the WWW browser 33, or being provided as in-line or plug-in software.

The operation control parameter file 51 stores various kinds of control parameters which are required for the operation of the slide show system. The bookmark data file 52 stores information such as the title of a page registered as a bookmark, the URL or the like. The web page data file 53 stores information of the pages which are downloaded from a WWW server, in order to use this information for the slide show.

The operation control parameter edition unit 41 sets various kinds of control parameters in the operation control parameter file 51, and also has a

function of changing these parameters. When a user instructs the registration of a bookmark, the bookmark registration unit 42 stores the information of the pages displayed by the WWW browser 33 in the bookmark data file 52. The bookmark display control unit 43 displays the thus-registered bookmark on a screen of the display device 24 according to the contents of the bookmark data file 52.

The automatic calling unit 44 automatically activates the web page display control unit 45, the BGM control unit 46, and the narration control unit 47, according to the contents of the operation control parameter file 51, and supplies necessary control parameters to these control units 45, 46, and 47.

The web page display control unit 45 reads the URL of a bookmark which is registered in the bookmark data file 52, according to the instructions of the automatic calling unit 44, and informs the thus-read URL to the WWW browser 33. The WWW browser 33 accesses the Internet 27 via the network interface unit 32 using the thus-informed URL or accesses the web page data file 53 using the thus-informed URL. Then, the web page display control unit 45 obtains information of the corresponding page and causes the display device 24 to display this information.

The BGM control unit 46 outputs predetermined BGM from the speaker 25 according to the instructions of the automatic calling unit 44. The narration control unit 47 outputs a predetermined narration from the speaker 25 according to the instructions of the automatic calling unit 44.

In this slide show system, an image display bookmark system (Japanese patent application No. 9-264478) which can be more easily handled, can be used other than a conventional bookmark system shown in Fig. 1. According to this image display bookmark system, the image of an actual web page is obtained, and data (an image icon) in which the image is made to be an icon, are registered as a bookmark. A user can easily access his or her desired page by clicking a bookmark which is displayed as an image icon.

Fig. 3 shows the display screen of a bookmark page using such an image icon system. This screen is displayed in such a way that a user performs an operation of displaying the edition screen of a bookmark from the WWW browser 33 or that a user performs an operation of easily displaying a bookmark using a pop-up window. This screen includes a folder display region 61 and an image display region 62.

In the folder display region 61, several folders

for storing a plurality of registered bookmarks are displayed, and generally a bookmark belonging to a single category is stored for each folder. In the image display region 62, a list of image icons 63
5 corresponding to the respective bookmarks in a folder which is selected by a user is displayed. Each of the image icons 63 is prepared by reducing the image of a web page corresponding to each bookmark.

According to this example, a folder such as
10 "Default" is selected by a user, and five image icons 63 corresponding to the five bookmarks in this folder are displayed. The folder "Default" also includes two folders such as "search" and "personal computer shop" in addition to these five bookmarks.

15 By selecting these folders in the folder display region 61, a user can display the image icons 63 of bookmarks stored in these folders. By selecting an image icon 63 in the image display region 62, a page, the URL of which is registered in a corresponding
20 bookmark, is automatically accessed to be displayed on a screen.

The slide show processing unit 31 shown in Fig. 2B can select a bookmark instead of a user and using the operation control parameter file 51, the bookmark data
25 file 52, and the web page data file 53 which

correspond to a bookmark page, and further can inform the URL of the thus-selected bookmark to the WWW browser 33.

Fig. 4 shows an example of the slide show screen to be displayed by the slide show system shown in Fig. 2B. This screen includes a web page 71, slide operation buttons 72, 73, and 74, and a termination button 75 (END).

A series of display sequence numbers is supplied to bookmarks to be used for the slide show. When a user pushes a reverse transmission button 72 in a manual mode, a page corresponding to a display sequence number which immediately precedes the currently displayed page, is displayed. When a user pushes a next transmission button 74, a page corresponding to a display sequence number which immediately follows the currently displayed page, is displayed. Here, the display sequence number represents a sequence for displaying the results obtained by accessing a WWW server when a plurality of pages are to be displayed. A pushing process of the button on a screen means an operation of clicking the button using a mouse or the like.

The termination button 75 is used when terminating a slide show in the manual mode. The stop button 73

is used for temporarily stopping the switching of pages in an automatic mode.

Here, operation buttons 72, 73, 74, and 75 are displayed on a screen, and a user clicks these buttons. However, these input operations can be performed according to an arbitrary method instructed from an arbitrary input device. For example, these operation functions can correspond to specific keys on a keyboard.

In the operation control parameter file 51, data such as shown in Fig. 5 are stored. In Fig. 5, AUTO corresponds to a flag indicating whether or not a display is performed in an automatic mode. When AUTO=Yes, an automatic mode is activated. When AUTO=No, a manual mode is activated.

MAXNUM is a parameter indicating the maximum value of a series of display sequence numbers. WAIT(i) is a parameter indicating a display time period of the page corresponding to a display sequence number i (i=1, 2, ..., MAXNUM). This display time period corresponds to a time interval between the display of a current page and that of the next page. Here, these parameters are set as follows: MAXNUM=20, and WAIT(i)=60 (seconds)

BGM(i) corresponds to a flag indicating whether or

not BGM is played when a page corresponding to the display sequence number *i* is displayed. When BGM(*i*)=Yes, BGM is played. When BGM(*i*)=No, BGM is not played. BGM_FILE(*i*) is a parameter indicating a file name of a file which stores the sound data of BGM to be played when a page corresponding to the display sequence number *i* is displayed. Here, this parameter is set to BGM_FILE(*i*)=song.avi.

NARRATION(*i*) corresponds to a flag indicating whether or not a narration is played back when a page corresponding to the display sequence number *i* is displayed. When NARRATION(*i*)=Yes, a narration is played back. When NARRATION(*i*)=No, a narration is not played back. NARRATION__FILE(*i*) is a parameter indicating the file name of a file which stores the sound data of a narration to be played back when a page corresponding to the display sequence number *i* is displayed. Here, this parameter is set to NARRATION FILE(*i*)=nal.avi.

As WAIT(*i*), BGM(*i*), BGM FILE(*i*), NARRATION(*i*), and NARRATION_FILE(*i*), different data can be set for each display sequence number *i*. The files of BGM and a narration are stored in, for example, the data storage device 22 shown in Fig. 2B.

Further, for example, data as shown in Fig. 6 are

stored in the bookmark data file 52. In Fig. 6, each set of bookmark data is composed of items such as "title", "URL", "image file name", "comment", "coordinate value", and "display sequence number".

5 In a column "title", the title data of a web page corresponding to each set of bookmark data are stored. In a column "URL", a URL of the web page is stored. A URL is generally described using a character string "http:" indicating an access destination on the Internet. When the access destination is data stored in the web page data file 53, the URL is described using the character string "file:" indicating a local file.

10 In a column "image file name", the file name of an image icon 63 shown in Fig. 3 is automatically named in order to be unique in a system, and the thus-named file name is stored. A "comment" column is used for a user to write a suitable comment. In a "coordinate value" column, the coordinate value of a position indicating the image icon 63 on a screen shown in Fig. 3 is stored. In a "display sequence number", a display sequence number specified by a user or a system is stored. The user can change this display sequence number via the bookmark display control unit 43.

25 Thus, the bookmark data file 52 stores a

correspondence relationship between the URL of a web page of each bookmark and a display sequence number. Therefore, the URL of a web page corresponding to the current display sequence number can be obtained by referring to the bookmark data file 52.

Next, display operations performed by the slide show system shown in Fig. 2B will be explained with reference to Fig. 7 to Fig. 11.

Fig. 7 is a flowchart showing the display control processing performed by the slide show processing unit 31. First, the automatic calling unit 44 reads the operation control parameter file 51 from the data storage device 22 (step S1), and checks the value of a flag AUTO (step S2). When AUTO=Yes, an automatic mode is activated, and automatic processing is performed (step S3). The details of this automatic processing will be explained later.

When AUTO=No, a manual mode is activated, and 0 is set to the control variable i indicating a display sequence number (step S4). Then, it is determined which button shown in Fig. 4 a user has pushed (step S5). When the user pushed the reverse transmission button 72, -1 is set to the variable Index indicating a difference of the display sequence number (step S6). When the user pushed the next transmission button 74,

1 is set to the variable Index (step S7). A value obtained adding the Index to the display sequence number is re-set as i , and the value of i is checked (step S9).

5 When $i \leq 0$, no display sequence numbers are present. Accordingly, it is set that $i=0$ (step S10), and processes in and after step S5 are repeated. When $i > \text{MAXNUM}$, no display sequence numbers corresponding to this value are present. Accordingly, it is set that
10 $i = \text{MAXNUM}$ (step S11), and processes in and after step S5 are repeated.

 In the case of $0 < i \leq \text{MAXNUM}$, the value of a flag BGM(i) corresponding to the regeneration number i is checked (step S12). When BGM(i)=Yes, the BGM control
15 unit 46 is activated, and the file name which is set in a BGM_FILE(i) is supplied to the unit 46.

 The BGM control unit 46 reads a BGM file corresponding to the thus-received file name (step S13), plays the sound data (step S14), and returns the
20 control to the automatic calling unit 44. Then, the automatic calling unit 44 repeats processes in and after step S15. When BGM(i)=No, processes in after step S15 are performed without activating the BGM control unit 46.

25 In step S15, the automatic calling unit 44 checks

the value of a flag NARRATION(i) corresponding to the display sequence number i. When NARRATION(i) =Yes, the narration control unit 47 is activated, and the file name which is set in a NARRATION_FILE(i) is supplied
5 to the unit 47.

The narration control unit 47 reads a narration file corresponding to the thus-received file name (step S16), played back the sound data (step S17), and returns the control to the automatic calling unit 44.
10 Then, the automatic calling unit 44 repeats processes in and after step S18. When NARRATION(i)=No, processes in after step S18 are performed without activating the narration control unit 47.

In step S18, the automatic calling unit 44
15 activates the web page display control unit 45, and instructs this unit 45 to display a web page corresponding to the display sequence number i. The web page display control unit 45 reads the URL of a bookmark of the display sequence number i from the
20 bookmark data file 52 (step S18), informs this URL to the WWW browser 33 (step S19), and returns the control to the automatic calling unit 44.

Then, the automatic calling unit 44 repeats processes in and after step S5. When a user pushes the
25 termination button 75, processing in a manual mode is

terminated.

In step S19 shown in Fig. 7, the WWW browser 33 to which a URL is informed performs display processing as shown in Fig. 8. The WWW browser 33 receives the
5 URL from the web page display control unit 45 (step S21), and accesses a WWW server or a local file stored in the web data file 53 which stores the web page (step S22).

Here, in the case where the URL starts with
10 "http:", a WWW server provided on the Internet 27 is accessed. In the case where the URL starts with "file:" the web page data file 53 is accessed. When information of the web page is obtained, this information is displayed on a screen of the display
15 device 24 (step S23), and processing is terminated.

When the web page display control unit 45 informs the URL to the WWW browser 33, a function of communicating between applications such as a DDE (dynamic data exchange) can be used.

20 The DDE is a kind of communication between processes, and exchanges data between applications using a shared memory. The application software provided on a transmission side can use the DDE for the real-time data exchange in the case where data are
25 transferred only once or where the contents of

updating processing are transmitted to the application software provided on a reception side when new data are available. Further, the DDE is automatically performed between applications without involving a user.

In step S3 shown in Fig. 7, the automatic calling unit 44 performs automatic processing as shown in Fig. 9. First, the automatic calling unit 44 sets a control variable i indicating a display sequence number to 0, and sets a variable Index indicating a difference of the display sequence number to 1 (step S31). Next, a value obtained by adding Index to the display sequence number i is re-set as i (step S32), and the processes in and after S33 are performed.

Here, the processes to be performed in steps S33 to S40 are the same as those performed in steps S12 to S19 shown in Fig. 7. The processing to be performed by the WWW browser 33 to which a URL is informed in step S40 is the same as that shown in Fig. 8.

Next, the automatic calling unit 44 checks a value of the display sequence number i (step S41). When $i < \text{MAXNUM}$, the automatic calling unit 44 waits for a time period which is set in $\text{WAIT}(i)$ (step S42), and repeats the processes in and after step S32. When i reaches MAXNUM, no display sequence numbers greater

than i are present, and accordingly the automatic processing is terminated.

When a user pushes the stop button 73 while the automatic processing is being operated, which is not specifically shown in Fig. 9, the automatic calling unit 44 can temporarily stop the display operation of the next page without regard to a time period which is set in the WAIT(i). In this case, the next transmission button 74, for example, is used for re-starting the display operations. When a user pushes the termination button 75, the automatic calling unit 44 can terminate the automatic processing. Thus, according to the display control processing in an automatic mode, a display sequence number is automatically incremented without a user pushing the operation buttons 72 and 74 so that a slide show is performed. Further, different BGM and different narrations can be played back for each web page to be displayed so that various kinds of slide shows can be performed.

In the above-mentioned embodiments, a different display interval, a different BGM file, and a different narration file are used for each display sequence number. When automatic processings are to be more easily performed, the same display interval, the

same BGM file, and the same narration file can be used.

Fig. 10 shows the data of the operation control parameter file 51 to be used for this automatic processing. In Fig. 10, the flag AUTO and the parameter MAXNUM is the same as the operation control parameter file 51 shown in Fig. 5.

A parameter WAIT indicates the display time period of a page which is common to all the display sequence numbers in an automatic mode. A flag BGM indicates whether or not BGM which is common to all the display sequence numbers is played. A parameter BGM_FILE indicates the file name of a file which stores sound data of the BGM. A flag NARRATION indicates whether or not a narration which is common to all the display sequence numbers is played back. A parameter NARRATION FILE indicates the file name of a file which stores sound data of the narration.

When the operation control parameter file 51 shown in Fig. 10 is used, the automatic calling unit 44 performs automatic processing as shown in Fig. 11, in step S3 of Fig. 7. First, the automatic calling unit 44 sets a control variable i to 0 which indicates a display sequence number, sets a variable Index to 1 which indicates a difference of the display sequence

number (step S51), and checks a value of the flag BGM (step S52). If BGM=Yes, the BGM control unit 46 is activated, and a file name which is set in BGM_FILE is supplied to the BGM control unit 46.

5 The BGM control unit 46 reads a BGM file corresponding to the thus-received file name (step S53), plays the sound data (step S54), and returns the control to the automatic calling unit 44. Then, the automatic calling unit 44 performs the processes in
10 and after step S55. When BGM=No, processes in and after step S55 are performed without activating the BGM control unit 46.

 In step S55, the automatic calling unit 44 checks the value of a flag NARRATION. When NARRATION=Yes, the
15 narration control unit 47 is activated, and a file name which is set in the NARRATION_FILE is supplied to the narration control unit 47.

 The narration control unit 47 reads a narration file corresponding to the thus-received file name
20 (step S56), plays back the sound data (step S57), and returns the control to the automatic calling unit 44. Then, the automatic calling unit 44 performs the processes in and after step S58. When NARRATION=No, processes in after step S58 are performed without
25 activating the narration control unit 47.

In step S58, the automatic calling unit 44 re-sets a value which is obtained by adding the Index to the display sequence number i , as i , and performs processes in and after step S59. Here, the processes to be performed in steps S59, S60, and S61 are the same as those performed in steps S39, S40, and S41 shown in Fig. 9. A processing to be performed by the WWW browser 33 to which the URL is informed in step S60 is the same as that shown in Fig. 8.

When $i < \text{MAXMUM}$ in step S61, the automatic calling unit 44 waits for a time period which is set in WAIT (step S62), and repeats the processes in and after step S58. In step S61, when i reaches MAXMUM, no sequence numbers greater than i are present, and accordingly the automatic processing is terminated.

According to this display control processing, the BGM and the narration are played back without being switched while the slide show is being performed, and only information of web pages is switched. Therefore, it is not necessary to provide a BGM file and a narration file for each web page to be displayed.

The slide show system shown in Fig. 2B can be configured using an information processing device (computer) as shown in Fig. 12. The information processing device shown in Fig. 12 includes a CPU

(central processing unit) 81, a memory 82, an input device 83, an output device 84, an external storage device 85, a medium driving device 86, and a network connection device 87. These devices are connected to each other via a bus 88.

The memory 82 includes, for example, a ROM (read only memory), a RAM (random access memory) and the like, and stores programs and data to be used for processings. The CPU 81 performs required processings by executing the programs using the memory 82.

The slide show processing unit 31, the operation control parameter edition unit 41, the bookmark registration unit 42, the bookmark display control unit 43, the automatic calling unit 44, the web page display control unit 45, the BGM control unit 46, and the narration control unit 47 shown in Fig. 2B, and the like correspond to software components which are described by a program, and each of these software components is stored in a specific program code segment in the memory 82.

The input device 83 corresponds to the input device 23 shown in Fig. 2B, and is used for the input of the instructions or the information transmitted from a user. The output device 84 includes the display device 24 and the speaker 25 shown in Fig. 2B, and is

used for the output of the question to a user, the information of a web page, BGM, a narration or the like.

The external storage device 85 is, for example,
5 a magnetic disk device, an optical disk device, a magneto-optical disk device or the like. The above-mentioned programs and data are stored in the external storage device 85, and if necessary, these items can be loaded to the memory 82 to be used. The external
10 storage device 85 can be used as the data storage device 22 shown in Fig. 2B.

The medium driving device 86 drives a portable storage medium 89, and accesses the storage contents. As the portable storage medium 89, an arbitrary
15 computer-readable storage medium such as a memory card, a floppy disk, a CD-ROM (compact disk read only memory), an optical disk, a magneto-optical disk or the like is used. The above-mentioned programs and data are stored in the portable storage medium 89, and
20 the thus stored items can be loaded to the memory 82 to be used, if necessary.

The network connection device 87 is controlled by the network interface unit 32 shown in Fig. 2B, is connected to the Internet 27 shown in Fig. 2B via an
25 arbitrary network such as a LAN (local area network)

or the like, and performs a data conversion to be required for communications. Further, the above-mentioned programs and data may be received from an external device so that these received items are
5 loaded to the memory 82 to be used, if necessary.

Fig. 13 shows computer readable storage media which can supply programs and data to the information processing device shown in Fig. 12. Programs and data which are stored in the portable storage medium 89 or
10 an external database 90 are loaded to the memory 82. Then, the CPU 81 executes the programs using these data and performs the required processings.

According to the present invention, information of one or more web pages can be easily and effectively
15 displayed when a presentation or a conference takes place, using a WWW browser which refers to the information of the WWW.

In a manual mode, for example, a slide operation button is provided so that web pages can be
20 sequentially accessed using existing bookmarks. Therefore, a user can smoothly progress a presentation without typing a URL.

Further, in an automatic mode, a plurality of web pages can be automatically displayed according to a
25 predetermined sequence and a display time period.

Therefore, a user can concentrate on a presentation without being directly involved in a display operation.

5 Further, since BGM and a narration can be automatically played back, an effective presentation can be performed according to the predetermined procedures.

What is Claimed is:

1. A slide show system comprising:

5 browser means for obtaining information using address information defined on an information network, and for outputting the thus-obtained information; and

10 control means for informing the address information to the browser means according to a predetermined output sequence, and for instructing output of information corresponding to the thus-informed address information.

2. The slide show system according to claim 1, further comprising:

15 storage means for storing a correspondence relationship between at least one piece of address information and a sequence number representing the output sequence, wherein

20 the control means refers to the correspondence relationship and determines address information to be informed to the browser means.

3. The slide show system according to claim 2, further comprising:

25 operation means for allowing a user to specify

information to be outputted next, wherein

the control means informs address information corresponding to the thus-specified information by the operation means to the browser means.

5

4. The slide show system according to claim 3, wherein the operation means specifies one of information pieces before and after information currently being outputted as the information to be
10 outputted next.

5. The slide show system according to claim 2, wherein the control means informs the at least one piece of address information to the browser means
15 according to the output sequence.

6. The slide show system according to claim 5, wherein the control means informs the at least one piece of address information to the browser means at
20 prescribed time intervals.

7. The slide show system according to claim 6 wherein the control means changes the time intervals according to the sequence number.

25

8. The slide show system according to claim 1, further comprising:

5 sound output means for outputting sound information including at least one of music and a narration, wherein

 the control means instructs the sound output means to output the sound information.

10 9. The slide show system according to claim 8, wherein the control means determines sound information to be outputted according to the sequence number of address information representing the output sequence.

15 10. The slide show system according to claim 1, wherein the browser means obtains information via a communication network using address information informed by the control means.

20 11. The slide show system according to claim 1, further comprising:

 storage means for storing information to be outputted corresponding to address information, wherein

25 the browser means obtains information which is stored in the storage means using address information

informed by the control means.

12. A computer-readable storage medium which stores a program for causing a computer to execute the steps of:

referring to a correspondence relationship between at least one piece of address information defined on an information network and a sequence number of a predetermined output sequence; and

- 10 informing address information corresponding to a current sequence number to a browser, and instructing output of information corresponding to the thus-informed address information.

13. A computer-readable storage medium which stores a program for causing a computer to execute the steps of:

referring to a correspondence relationship between at least one piece of address information defined on an information network and a sequence number of a predetermined output sequence;

obtaining information using address information corresponding to a current sequence number; and

outputting the thus-obtained information.

14. A slide show method comprising the steps of:

preparing a correspondence relationship between at least one piece of address information defined on an information network and a sequence number of a predetermined output sequence;

5

obtaining address information corresponding to a current sequence number with reference to the correspondence relationship;

10

obtaining information using the address information corresponding to the current sequence number; and

presenting the thus-obtained information.

Abstract of the Disclosure

When a presentation is performed using a web browser, in a manual mode, the display sequence of web
5 pages registered in a bookmark list is specified using
an operation button, and in an automatic mode, a
plurality of pages registered in a bookmark list are
automatically displayed in a predetermined sequence.
Further, background music and a narration are also
10 automatically played back.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4

FLAG NAME=FLAG	MEANING
AUTO=Yes	AUTOMATIC DISPLAY IS PERFORMED? Yes OR No
MAXNUM=20	MAXIMUM VALUE OF DISPLAY SEQUENCE NUMBER
WAIT(i)=60	IN CASE OF AUTOMATIC DISPLAY, INTERVAL BETWEEN DISPLAYS (SECONDS) (i=1..MAXNUM)
BGM(i)=Yes	BGM IS PLAYED? Yes OR No (i=1..MAXNUM)
BGM_FILE(i)=song,avi	FILE OF BGM (i=1..MAXNUM)
NARRATION(i)=Yes	NARRATION IS PLAYED BACK? Yes OR No (i=1..MAXNUM)
NARRATION_FILE(i)=na1,avi	FILE OF NARRATION (i=1..MAXNUM)

FIG. 5

TITLE	URL	IMAGE FILE NAME	COMMENT	COORDINATE VALUE	DISPLAY SEQUENCE NUMBER
xxx HOME Page	http://www.xxx.co.jp	xxx1.bmp	hoge hoge. . .	10, 10	1
yyy HOME Page	http://www.yyy.co.jp	xxx3.bmp	hoge hoge. . .	40, 10	3
zzz HOME Page	file:///D:/cache/file1.html	xxx4.bmp	hoge hoge. . .	80, 10	5
:	:	:	:	:	:

FIG. 6




FIG. 7




FIG. 8




FIG. 9

FLAG NAME=FLAG	MEANING
AUTO=Yes	AUTOMATIC DISPLAY IS PERFORMED? Yes OR No
MAXNUM=20	MAXIMUM VALUE OF DISPLAY SEQUENCE NUMBER
WAIT=60	IN CASE OF AUTOMATIC DISPLAY, INTERVAL BETWEEN DISPLAYS (SECONDS)
BGM=Yes	BGM IS PLAYED? Yes OR No
BGM_FILE=song.avi	FILE OF BGM
NARRATION=Yes	NARRATION IS PLAY BACK? Yes OR No
NARRATION_FILE=nal.avi	FILE OF NARRATION

FIG. 10




FIG. 11




FIG. 12




FIG. 13

Declaration and Power of Attorney For Patent Application**特許出願宣言書及び委任状****Japanese Language Declaration****日本語宣言書**

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

SLIDE SHOW SYSTEM AND METHOD
USING A BROWSER

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約
国際出願番号を _____ とし、
(該当する場合) _____ に訂正されました。

☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、
内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of
the above identified specification, including the claims, as
amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されると
おり、特許資格の有無について重要な情報を開示する義務が
あることを認めます。

I acknowledge the duty to disclose information which is material to
patentability as defined in Title 37, Code of Federal Regulations,
Section 1.56.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づき国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s)

外国での先行出願

10-213799

(Number)

(番号)

Japan

(Country)

(国名)

(Number)

(番号)

(Country)

(国名)

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

☐

29th/July/1998

(Day/Month/Year Filed)

(出願年月日)

(Day/Month/Year Filed)

(出願年月日)

☐

私は、第35編米国法典119条(e)項に基づいて下記の米国外特許出願規定に記載された権利をここに主張いたします。

(Application No.)

(出願番号)

(Filing Date)

(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)

(出願番号)

(Filing Date)

(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国外特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国外特許出願に開示されていない限り、その先行米国外出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.)

(出願番号)

(Filing Date)

(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Status: Patented, Pending, Abandoned)

(現況: 特許許可済、保属中、放棄済)

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Status: Patented, Pending, Abandoned)

(現況: 特許許可済、保属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の表明を行えば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の
手続きを米特許商標局に対して遂行する弁理士または代理人
として、下記の者を指名いたします。(弁理士、または代理
人の氏名及び登録番号を明記のこと)

James D. Halsey, Jr., 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; John C. Garvey, 28,607; J. Randall Beckers,
30,358; William F. Herbert, 31,024; Richard A. Gollhofer, 31,106; Mark J. Henry, 36,162; Gene M. Garner II, 34,172; Michael D.
Stein, 37,240; Paul I. Kravetz, 35,230; Gerald P. Joyce, III, 37,648; Todd E. Marlette, 35,269; Harlan B. Williams, Jr., 34,756;
George N. Stevens, 36,938; Michael C. Soldner, 41,455; Norman L. Ourada, 41,235; Kevin R. Spivak, P-43,148; and William M.
Schertler, 35,348 (agent)

書類送付先

POWER OF ATTORNEY: As a named inventor, I hereby appoint
the following attorney(s) and/or agent(s) to prosecute this
application and transact all business in the Patent and Trademark
Office connected therewith (list name and registration number)

Send Correspondence to:

STAAS & HALSEY
700 Eleventh Street, N.W.
Suite 500
Washington, D.C. 20001

直接電話連絡先: (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

STAAS & HALSEY
(202) 434-1500

唯一または第一発明者名	Full name of sole or first inventor
	Hironori KANNO
発明者の署名	Inventor's signature
日付	Date
	<i>Hironori Kanno</i> January 12, 1999
住所	Residence
	Miyagi, Japan
国籍	Citizenship
	Japan
私書箱	Post Office Address
	c/o FUJITSU TOHOKU SYSTEMS ENGINEERING LIMITED, 3-5, Ichibancho 3-chome, Aoba-ku, Sendai-shi, Miyagi 980-8520, Japan
第二共同発明者	Full name of second joint inventor, if any
	Yoshiyuki HIRASHIMA
第二共同発明者	Second inventor's signature
日付	Date
	<i>Yoshiyuki Hirashima</i> January 12, 1999
住所	Residence
	Miyagi, Japan
国籍	Citizenship
	Japan
私書箱	Post Office Address
	c/o FUJITSU TOHOKU SYSTEMS ENGINEERING LIMITED, 3-5, Ichibancho 3-chome, Aoba-ku, Sendai-shi, Miyagi 980-8520, Japan

(第三以降の共同発明者についても同様に記載し、署名をす
ること)

(Supply similar information and signature for third and subsequent
joint inventors.)

第三共同発明者		Full name of third joint inventor, if any Mikio FURUYAMA	
第三共同発明者	日付	Third inventor's signature <i>Mikio Furu Furuyama</i>	Date January 12, 1999
住 所		Residence Miyagi, Japan	
国 籍		Citizenship Japan	
私書箱		Post Office Address c/o FUJITSU TOHOKU SYSTEMS ENGINEERING LIMITED, 3-5, Ichibancho 3-chome, Aoba-ku, Sendai-shi, Miyagi 980-8520, Japan	
第四共同発明者		Full name of fourth joint inventor, if any	
第四共同発明者	日付	Fourth inventor's signature	Date
住 所		Residence	
国 籍		Citizenship	
私書箱		Post Office Address	

第五共同発明者		Full name of fifth joint inventor, if any	
第五共同発明者	日付	Fifth inventor's signature	Date
住 所		Residence	
国 籍		Citizenship	
私書箱		Post Office Address	
第六共同発明者		Full name of sixth joint inventor, if any	
第六共同発明者	日付	Sixth inventor's signature	Date
住 所		Residence	
国 籍		Citizenship	
私書箱		Post Office Address	

(第七以降の共同発明者についても同様に
記載し、署名をすること)

(Supply similar information and signature for seventh and subsequent joint inventors.)